

DEHUMIDIFICATION UNIT



RENTAL PACKAGE

OCDH-5000S

Desiccant Dehumidifier

APPLICATIONS:

- Mold/Fungus Prevention
- Surface Preparation and Coating
- Restoration Drying
- Corrosion Prevention
- Electronics Prevention
- Power Plant Lay-Up
- Pharmaceutical
- Candy Manufacturing

PRODUCT FEATURES:

- Operator Interface with Touch Screen Control:
 1. Monitor Temperature
 2. Monitor Airflow
 3. Make Adjustments Per Customer Requirements
- Process fan VFD Control Manually Adjustable
- Reactivation Fan VFD Control Automatic
- Reactivation Air Temperature and Fan Speed controlled through PLC to Maintain Maximum Performance
- Non-rusting Aluminum Construction
- Lightweight/Small Footprint
- User Friendly and Reliable Operation

OPERATING DATA:

Dehumidifier	Model Process Air Flow Reactivation Heat Source Total Static Available	OCDH-5000S 5000 CFM 115 kW 8 inch WC
Dimensions	Length Width Height Weight	10' 5' 6' 2,100 lbs.
Electric	Volts Phases Hz FLA	480 3 60 180 Amps
Included Options	Handling Connection Type Outlet Size Inlet Size	Four Way Fork Pockets & Overhead Lifting Cam-lock 19" 19"