



The Cat® C15 Industrial Diesel Engine is offered in ratings ranging from 328-444 kW (440-595 bhp) @ 1800-2100 rpm. These ratings meet China Stage II, U.S. EPA Tier 3 equivalent, and EU Stage IIIA equivalent emission standards. Industries and applications powered by C15 engines include Agriculture, Ag Tractors, Aircraft Ground Support, Bore/Drill Rigs, Chippers/Grinders, Combines/Harvesters, Compactors/Rollers, Compressors, Construction, Cranes, Crushers, Dredgers, Forestry, General Industrial, Hydraulic Power Units, Irrigation Equipment, Loaders/Forwarders, Material Handling, Mining, Mobile Earthmoving Equipment, Paving Equipment, Pumps, Shovels/Draglines, Surface Hauling Equipment and Trenchers.

Specifications

Power Rating		
Maximum Power	444 kW	595 HP
Maximum Torque	2717 Nm @ 1400 rpm	2004 lb-ft @ 1400 rpm
Rated Speed	1800-2100 rpm	
Minimum Power	328 kW	440 HP

Emission Standards	
Emissions	China Nonroad III, U.S. EPA Tier 3 Equivalent, EU Stage IIIA Equivalent

General		
Engine Configuration	Inline 6, 4-Stroke-Cycle Diesel	
Bore	137 mm	5.4 in
Stroke	171 mm	6.8 in
Displacement	15.2 l	927.6 in ³
Compression Ratio	18.0:1	
Aspiration	Turbocharged Aftercooled (TA)	
Combustion System	Direct Injection	
Rotation from Flywheel End	Counterclockwise	
Aftertreatment	-	

Engine Dimensions - Approximate		
Length	1377 mm	54.2 in
Width	919 mm	36.2 in
Height	1226 mm	48.3 in
Weight - Net Dry - Basic Operating Engine Without Optional Attachments	1469 kg	3239 lb

Benefits and Features

Reliable, Quiet and Durable Power

World-class manufacturing capability and processes coupled with proven core engine designs assure reliability, quiet operation, and many hours of productive life.

Broad Application Range

Industry leading range of factory configurable ratings and options for agricultural, material handling, construction, mining, aircraft ground support, and other industrial applications.

Package Size

Exceptional power density enables standardization across numerous applications. Multiple installation options minimize total package size. Ideal for equipment with narrow engine compartments.

World-class Product Support Offered Through Global Cat Dealer Network

- Scheduled maintenance, including SOSSM sample
- Customer Support Agreements (CSA)
- Caterpillar Extended Service Coverage (ESC)
- Superior dealer service network
- Extended dealer service network through the Cat Industrial Service Distributor (ISD) program

Standard Equipment

Air Inlet System

- Turbocharged
- Air-to-Air Aftercooled

Control System

- Electronic governing, PTO speed control
- Programmable ratings
- Automatic altitude compensation
- Power compensation for fuel temperature
- Programmable low and high idle and total engine limit
- Electronic diagnostics and fault logging
- Engine monitoring system SAE J1939 broadcast and control
- ADEM™ A4 Electronic Control Unit (ECU)

Cooling System

- Thermostats and housing, vertical outlet
- Jacket water pump, centrifugal
- Water pump, inlet

Exhaust System

- Exhaust manifold, dry
- Optional exhaust outlet

Flywheels and Flywheel Housing

- SAE No. 1 flywheel housing

Fuel System

- MEUI injection

- Fuel filter, secondary (2 micron)
- Fuel filter, tertiary (2 micron)
- ACERT™ Technology
- Fuel transfer pump
- Fuel priming pump

Lube System

- Crankcase breather
- Oil cooler
- Oil filler
- Lube oil filter
- Front sump oil pan
- Oil dipstick
- Gear driven oil pump

General

- Vibration damper
- Lifting eyes
- Cold start capability to -20° C (-4° F)
- Paint: Caterpillar yellow, with optional colors available at request

The International System of Units (SI) is used in this publication. CAT, CATERPILLAR, their respective logos, ADEM, EUI, S•O•S, "Caterpillar Yellow" and the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.